


HOLE TABLE			
HOLE	XDIM	YDIM	DESCRIPTION
A1	-8.055	-10.897	Ø.332 THRU
A2	8.055	-10.897	Ø.332 THRU
A3	-8.368	-7.913	Ø.332 THRU
A4	8.368	-7.913	Ø.332 THRU
A5	-8.681	-4.930	Ø.332 THRU
A6	8.681	-4.930	Ø.332 THRU
A7	-8.994	-1.946	Ø.332 THRU
A8	8.994	-1.946	Ø.332 THRU
A9	-8.400	.000	Ø.332 THRU
A10	-5.600	.000	Ø.332 THRU
A11	-2.800	.000	Ø.332 THRU
<b>A12</b>	.000	.000	Ø.332 THRU
A13	2.800	.000	Ø.332 THRU
A14	5.600	.000	Ø.332 THRU
A15	8.400	.000	Ø.332 THRU
A16	-1.500	1.139	Ø.332 THRU
A17	1.500	1.139	Ø.332 THRU
A18	-1.500	2.514	Ø.332 THRU
A19	1.500	2.514	Ø.332 THRU
A20	-1.500	3.889	Ø.332 THRU
A21	1.500	3.889	Ø.332 THRU



DRAWN Gary Swift TUNL	7/10/2019	<b>SoLID HGC</b>		
1-919-660-2668				
Material: Alum 6061-T651		TITLE Proto Assy Shell Back Plate Extension		
Unless Otherwise Specified Tolerances are: .xx = ± .01    Angles = ± 0.1° .xxx = ± .005	Break Sharp Edges: 0.010  Deburr Holes: .015			
Dim in Inches		SIZE <b>B</b>	DWG NO <b>SP-10-01-15</b>	REV
		SCALE 1 / 4	SHEET 2 OF 2	